



Ametalin

Performance insulation for a greener world

Temperate Insulation Range

SilverSark® and VapourTech® RWC for roofs

VapourTech® range for walls and

SilverWrap® Micro-perforated range

For brick veneer and drained cavity walls.



Residential & Commercial

Reflective vapour and weather barrier insulation and vapour permeable membranes. For use in ABCB climate zones 4 - 5

Ametalin
Performance insulation for a greener world

SilverSark® HD
Heavy Duty

81 m² COVERAGE WIDTH: 1350 mm
LENGTH: 60 m AREA: 81 m²

Reflective roof and wall insulation
For tile or metal roofs and walls in residential and commercial buildings

- > Class 2 Vapour Barrier, Air and Water Barrier
- > Superior strength and puncture resistance
- > Ideal for all BALs in bushfire-prone areas

APPLICATIONS (WHERE THIS PRODUCT CAN BE USED)	1	2	3	4	5	6	7	8
ROOF (Metal)	1	2	3	4	5	6	7	8
ROOF (Tile)	1	2	3	4	5	6	7	8
WALL (Internal)	1	2	3	4	5	6	7	8
WALL (External)	1	2	3	4	5	6	7	8
WALL (Cavity)	1	2	3	4	5	6	7	8

Ametalin
Performance insulation for a greener world

VapourTech® RWC Roof Wall Commercial
Medium Duty

45 m² COVERAGE WIDTH: 1500 mm
LENGTH: 30 m AREA: 45 m²

Vapour permeable roof and wall insulation
For use in commercial and residential roofs, facades and wall systems in ABCB Climate Zones 2-8

- > Class 4 Vapour Permeable, Air and Water Barrier
- > Advanced weather barrier and vapour control membrane
- > Reinforced four-layer construction for high strength, tear and puncture resistance
- > Ideal for all BALs in bushfire-prone areas
- > High UV resistance - up to 90 days

APPLICATIONS (WHERE THIS PRODUCT CAN BE USED)	2	3	4	5	6	7	8
ROOF (Metal)	2	3	4	5	6	7	8
ROOF (Tile)	2	3	4	5	6	7	8
WALL (Internal)	2	3	4	5	6	7	8
WALL (External)	2	3	4	5	6	7	8

Ametalin
Performance insulation for a greener world

VapourTech® Wall
Light Wall Duty

45 m² COVERAGE WIDTH: 1500 mm
LENGTH: 30 m AREA: 45 m²

Vapour permeable wall insulation
For use behind all types of cladding and in all wall systems in ABCB Climate Zones 2-8

- > Class 4 Vapour Permeable, Air and Water Barrier
- > Advanced weather barrier and vapour control membrane
- > Triple layer construction for durability
- > High wind load performance to 3.45 kPa
- > Ideal for all BALs in bushfire-prone areas
- > High UV resistance - up to 90 days

APPLICATIONS (WHERE THIS PRODUCT CAN BE USED)	2	3	4	5	6	7	8
WALL (Internal)	2	3	4	5	6	7	8
WALL (External)	2	3	4	5	6	7	8

Ametalin
Performance insulation for a greener world

SilverWrap® xRS MD Micro-perforated
Extra R-value Medium Duty

81 m² COVERAGE WIDTH: 1350 mm
LENGTH: 60 m AREA: 81 m²

Vapour Permeable outward reflective wall insulation
For use in brick veneer and drained cavity wall systems in residential and commercial buildings

- > Innovative reflective design, converts brick veneer steel frame into the equivalent of timber-frame for NCC energy efficiency
- > Class 3 Vapour Permeable, Air Barrier
- > Non-water Barrier
- > Strong and light weight

APPLICATIONS (WHERE THIS PRODUCT CAN BE USED)	1	2	3	4	5
WALL (Internal)	1	2	3	4	5
WALL (External)	1	2	3	4	5

For full product range and approved accessories please visit,

www.ametalin.com



Ametalin

Performance insulation for a greener world

CeaseFire®

The ultimate fire resisting, weather-proofing and vapour management membrane for NCC DtS Non-combustible and fire-resisting systems in Australian buildings.



Extra Heavy Duty

Fire resistant roof & wall insulation

For use in DtS fire resisting constructions in ABCB climate zones 2-8

DtS Non-combustible

Class 4 Vapour Permeable

Air and Water Barrier

Group 1 fire performance
for linings

Ember proof



Available roll size: **1500 mm x 30 m (45 m²)**



Ametalin

Performance insulation for a greener world

VapourTech® RWC Roof Wall Commercial

Advanced weather barrier and vapour control membrane for condensation management in roofs and walls.



Medium Duty

Vapour permeable roof and wall Insulation

For use in commercial and residential roofs, facades and wall systems in ABCB Climate Zones 2-8.

Class 4 Vapour Permeable

Air and Water Barrier

Reinforced four-layer construction for high strength, tear and puncture resistance

Ideal for all BALs in bushfire-prone areas

High UV resistance - up to 90 days



Available at
BUNNINGS
warehouse

Available roll size: **1500 mm x 30 m (45 m²)**



Ametalin

Performance insulation for a greener world

VapourTech® Wall

Next generation permeable air barrier technology for walls.



Light Wall Duty

Vapour Permeable wall insulation

For use behind all types of cladding and in all wall systems in climate zones 2-8.

Class 4 Vapour Permeable

Advanced water, air and vapour control membrane

Triple layer construction for durability

Low Flammability, suitable for all BALs in bushfire-prone areas



Available roll size: **1370 mm x 30 m (41 m²)** | **1500 mm x 30 m (45 m²)**



Ametalin

Performance insulation for a greener world

VapourTech® Brane® VHP

Superior vapour permeance technology for condensation management in walls



Light Wall Duty

Vapour Permeable wall insulation

For moisture control behind all types of cladding and in all wall systems in Climate Zone 2-8

Low Flammability

Class 4 Vapour Permeable

Water Barrier

Triple layer construction for durability



Available at
BUNNINGS
warehouse

Available roll size:

- 1370 mm x 30 m (41 m²)
- 2740 mm x 30 m (82.2m²)
- 1500 mm x 30 m (45 m²)



Ametalin

Performance insulation for a greener world

Micro-perforated Insulation Range

Ametalin SilverWrap™ xRS Micro-perforated, FireSark® Micro-perforated, SilverWrap™ xR Micro-perforated & SilverWrap™ Micro-perforated



Residential & Commercial

Vapour Permeable reflective wall insulation

For use in brick veneer and drained cavity wall systems in residential and commercial buildings.

Ametalin
Performance insulation for a greener world

FireSark® Micro-perforated
Extra Heavy Duty

40.5m² COVER
WIDTH: 1350 mm
LENGTH: 30 m
AREA: 40.5 m²

Fire resistant permeable reflective wall insulation

For use in Non-Combustible constructions in multi-storey residential and commercial buildings

- Ember-proof
- Ideal for all BAL zone wall systems to FZ bushfire-prone areas
- Air Barrier, Class 3 Vapour Permeable
- Ultra-strong material
- Superior heat resistance
- 97% Reflective

Ametalin
Performance insulation for a greener world

SilverWrap™ XHD Micro-perforated
Extra Heavy Duty

81m² COVER
WIDTH: 1350 mm
LENGTH: 60 m
AREA: 81 m²

Vapour Permeable reflective wall insulation

For use in brick veneer and drained cavity wall systems in residential and commercial buildings

- Micro-perforated to Class 3 Vapour Permeable
- Superior strength, light weight
- Air Barrier
- Low Flammability, suitable for all BALs in bushfire-prone areas
- 97% reflective

Ametalin
Performance insulation for a greener world

SilverWrap™ xR HD Micro-perforated
Extra R-value Heavy Duty

40.5m² COVER
WIDTH: 1350 mm
LENGTH: 30 m
AREA: 40.5 m²

Vapour Permeable reflective wall insulation

For use in brick veneer and drained cavity wall systems in residential and commercial buildings

- Premium double-sided foil
- Micro-perforated to Class 3 Vapour Permeable
- Superior strength, lightweight
- Air Barrier
- Low Flammability, suitable for all BALs in bushfire-prone areas

Ametalin
Performance insulation for a greener world

SilverWrap™ xRS MD Micro-Perforated
Extra R-value Medium Duty

81m² COVER
WIDTH: 1350 mm
LENGTH: 60 m
AREA: 81 m²

Vapour Permeable reflective wall insulation

For use in brick veneer and drained cavity wall systems in residential and commercial buildings

- Innovative low-glare, high IR reflection technology
- Micro-perforated to Class 3 Vapour Permeable
- Ideal for drained cavity systems in Climate zones 6-8
- Strong and light weight
- Air Barrier
- Low Flammability, suitable for all BALs in bushfire-prone areas

For full product range and approved accessories please visit,

www.ametalin.com



Ametalin

Performance insulation for a greener world

SilverWrap™ xRS Micro-perforated

Extra R-value Vapour Permeable reflective wall insulation.



Medium Duty

Vapour permeable reflective wall insulation

For use in brick veneer and drained cavity wall systems in residential and commercial buildings.

Innovative low-glare,
high IR reflection ink technology

Micro-perforated to Class 3 Vapour
Permeable and Air Barrier

Ideal for drained cavity systems
in Climate Zones 6 - 8

Air Barrier

Low Flammability, suitable for all
BALs in bushfire-prone areas



Available roll size: **1350 mm x 30 m (40.5 m²) | 1350 mm x 60 m (81 m²)**



Ametalin

Performance insulation for a greener world

FireSark[®] Micro-perforated

Premium reflective non-combustible vapour permeable wall wrap.



Extra Heavy Duty

Fire resistant permeable reflective wall insulation

For use in Non-Combustible constructions in multi-storey residential and commercial buildings.

Ember-proof

Ideal for all BAL zones wall systems to FZ bushfire-prone areas

Air Barrier, Class 3 Vapour Permeable

Superior heat resistance

97% reflective



Available roll size: **1350 mm x 30 m (40.5 m²)**



Ametalin

Performance insulation for a greener world

SilverWrap™ LD Micro-perforated

High-tech reflective permeable wall wrap.



Light Duty

Vapour Permeable reflective wall insulation

For use in brick veneer and drained cavity wall systems in residential and commercial buildings. ABCB Climate Zones 2 - 8.

Micro-perforated to
Class 4 Vapour Permeable

Strong and light weight

Air Barrier

Low Flammability, suitable for all
BALs in bushfire-prone areas

97% reflective



Available roll size: **1500 mm x 30 m (45 m²) | 1350 mm x 60 m (81 m²)**



Ametalin

Performance insulation for a greener world

SilverWrap™ MD Micro-perforated

High-tech reflective permeable wall wrap.



Medium Duty

Vapour Permeable reflective wall insulation

For use in brick veneer and drained cavity wall systems in residential and commercial buildings. ABCB Climate Zones 2-8.

Micro-perforated to
Class 4 Vapour Permeable

Strong and light weight

Air Barrier

Low Flammability, suitable for all
BALs in bushfire-prone areas

97% reflective



Available roll size: **1350 mm x 30 m (40.5 m²) | 1500 mm x 30 m (45 m²)**
1350 mm x 60 m (81 m²)



Ametalin

Performance insulation for a greener world

SilverWrap™ xR Micro-perforated HD

Extra R-value Vapour Permeable reflective wall insulation.



Heavy Duty

Vapour permeable reflective wall insulation

For use in brick veneer and drained cavity wall systems in residential and commercial buildings. ABCB Climate Zones 2 - 8.

Premium double-sided foil

Micro-perforated to
Class 4 Vapour Permeable

Superior strength, lightweight

Air Barrier

Low Flammability, suitable for
all BALs in bushfire-prone areas



Available roll size: **1350 mm x 30 m (40.5 m²)**